

# Alert Endpoints

<b>Summary</b>	Provides list of alerts																													
<b>Description</b>	This endpoint returns list of alerts. The endpoint is available only to authenticated users.																													
<b>URL</b>	/alerts																													
<b>Method</b>	GET																													
<b>Available in version</b>	v2																													
<b>Headers</b>	<table border="1"> <thead> <tr> <th>Name</th> <th>Mandatory</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Accept</td> <td>No</td> <td> <table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table> <p>Default: JSON</p> <p>Note: It is recommended that client application not rely on default output and always pass valid Accept header.</p> </td> </tr> <tr> <td>X-SubSiteCode</td> <td>No</td> <td>Default value: LI</td> </tr> <tr> <td>Authorization</td> <td>Yes</td> <td>e.g. Bearer eyJ0eXAI0iJKV1QilCJhbGciOiJIUz11NiJ9.eyJza..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c</td> </tr> </tbody> </table>					Name	Mandatory	Description	Accept	No	<table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table> <p>Default: JSON</p> <p>Note: It is recommended that client application not rely on default output and always pass valid Accept header.</p>	Output format	value	JSON	application/json	XML	text/xml	X-SubSiteCode	No	Default value: LI	Authorization	Yes	e.g. Bearer eyJ0eXAI0iJKV1QilCJhbGciOiJIUz11NiJ9.eyJza..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c							
Name	Mandatory	Description																												
Accept	No	<table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table> <p>Default: JSON</p> <p>Note: It is recommended that client application not rely on default output and always pass valid Accept header.</p>	Output format	value	JSON	application/json	XML	text/xml																						
Output format	value																													
JSON	application/json																													
XML	text/xml																													
X-SubSiteCode	No	Default value: LI																												
Authorization	Yes	e.g. Bearer eyJ0eXAI0iJKV1QilCJhbGciOiJIUz11NiJ9.eyJza..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c																												
<b>Parameters</b>	<table border="1"> <thead> <tr> <th>Name</th> <th>Located in</th> <th>Mandatory</th> <th>Schema</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>start</td> <td>Querystring</td> <td>No</td> <td>int</td> <td>Default value: 0.  Value must be greater than or equal to 0.</td> </tr> <tr> <td>rows</td> <td>Querystring</td> <td>No</td> <td>int</td> <td>Default value: 20.  Value must be less than or equal to 40.</td> </tr> <tr> <td>sort</td> <td>Querystring</td> <td>No</td> <td>string</td> <td>Default value: NAME  Allowed sorting types are: <ul style="list-style-type: none"> <li>NAME</li> <li>DATE_DESC</li> </ul> </td> </tr> <tr> <td>q</td> <td>Querystring</td> <td>No</td> <td>string</td> <td>Search text q: it is optional. and no default value</td> </tr> </tbody> </table>					Name	Located in	Mandatory	Schema	Description	start	Querystring	No	int	Default value: 0.  Value must be greater than or equal to 0.	rows	Querystring	No	int	Default value: 20.  Value must be less than or equal to 40.	sort	Querystring	No	string	Default value: NAME  Allowed sorting types are: <ul style="list-style-type: none"> <li>NAME</li> <li>DATE_DESC</li> </ul>	q	Querystring	No	string	Search text q: it is optional. and no default value
Name	Located in	Mandatory	Schema	Description																										
start	Querystring	No	int	Default value: 0.  Value must be greater than or equal to 0.																										
rows	Querystring	No	int	Default value: 20.  Value must be less than or equal to 40.																										
sort	Querystring	No	string	Default value: NAME  Allowed sorting types are: <ul style="list-style-type: none"> <li>NAME</li> <li>DATE_DESC</li> </ul>																										
q	Querystring	No	string	Search text q: it is optional. and no default value																										

**Supported response formats**

Format	Mime type
JSON	application/json
XML	text/xml

**Responses**

Code	Description	Schema (JSON)
200	Success. Provide total alert count, list of alert.	<pre>{   "Count": int,   "Alerts": [     {       "Id": int,       "Name</pre>

```
" : s t r i n g , " s e a r c h T Y P e " : s t r i n g , " s h a r e d " : b o o l e a n , " T o t
```

a  
l  
E  
M  
a  
i  
l  
S  
e  
n  
t  
" :  
i  
n  
t  
" D  
a  
t  
e  
C  
r  
e  
a  
t  
e  
Q  
" :  
s  
t  
r  
i  
n  
g  
(  
U  
F  
C  
F  
O  
R  
M  
a  
t  
)  
,  
" S  
e

```
a  
r  
c  
h  
T  
e  
x  
t  
":  
s  
t  
r  
i  
n  
g  
,  
"  
F  
i  
l  
t  
e  
r  
":  
s  
t  
r  
i  
n  
g  
}  
  
]  
}
```

400

Bad request. Client receives this code when data validation fails.

```
{  
  
"  
M  
e  
s  
s  
a  
g  
e
```

```
" : s t r i n g , " M o d e l S t a t e " : {  
  " < P A R A M E T E R _ N A M E > " : [ s t r i n g
```

		<pre>] }</pre>
401	Unauthorized Access. Client receives this code when "Authorization" header is passed in request but token validation fails	<pre>{   "   M   e   s   s   a   g   e   "   :   s   t   r   i   n   g }</pre>
500	Internal error	

```
{
  "code" : string,
  "message" : string,
  "error" : string
}
```

**Sample Call**

```

var settings = {
  "crossDomain": true,
  "url": "https://api.
legalintelligence.com/alerts",
  "method": "GET",
  "headers": {
    "X-SubSiteCode": "LI",
    "Authorization": "Bearer
eyJ0eXAiOiJKV1QiLCJhbGciOiJIUz
I1NiJ9.eyJsaTp..MX0.
6pNugdmqnmix38pETbyGI_zchmBCBw
FQt_tFNBTk55c",
    "Accept": "application
/json"
  }
}

$.ajax(settings).done
(function (response) {
  console.log(response);
});

```

**Response Models**

Response		
Field	Type	Description
Count	int	Total count of alert.
Alerts	object[]	List of Alert

Alert		
Field	Type	Description
Id	int	Alert identifier
Name	string	Name of alert
SearchType	string	Search type of alert
Shared	boolean	Alert is shared or not
TotalEmailSent	int	Total number of email sent of alert
DateCreated	string	Created date of alert in UTC date format
SearchText	string	Search text of alert
Filters	string[]	Filters applied in alert

**Notes****Summary**

Provides list of alert's viewId

**Description**

This endpoint provides list of alert's viewId. This endpoint is available to authenticated users.

<b>URL</b>	/alerts/<id>/views																				
<b>Method</b>	GET																				
<b>Available in version</b>	v2																				
<b>Headers</b>	<table border="1"> <thead> <tr> <th>Name</th> <th>Mandatory</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Accept</td> <td>Yes</td> <td> <table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table> </td> </tr> <tr> <td>X-SubSiteCode</td> <td>No</td> <td>Default value: LI</td> </tr> <tr> <td>Authorization</td> <td>Yes</td> <td>e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJsa..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c</td> </tr> </tbody> </table>	Name	Mandatory	Description	Accept	Yes	<table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table>	Output format	value	JSON	application/json	XML	text/xml	X-SubSiteCode	No	Default value: LI	Authorization	Yes	e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJsa..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c		
Name	Mandatory	Description																			
Accept	Yes	<table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table>	Output format	value	JSON	application/json	XML	text/xml													
Output format	value																				
JSON	application/json																				
XML	text/xml																				
X-SubSiteCode	No	Default value: LI																			
Authorization	Yes	e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJsa..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c																			
<b>Parameters</b>	<table border="1"> <thead> <tr> <th>Name</th> <th>Located in</th> <th>Mandatory</th> <th>Schema</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>&lt;ID&gt;</td> <td>URL</td> <td>Yes</td> <td>int</td> <td>Alert identifier</td> </tr> <tr> <td>start</td> <td>Querystring</td> <td>No</td> <td>int</td> <td>Default value: 0.</td> </tr> <tr> <td>rows</td> <td>Querystring</td> <td>No</td> <td>int</td> <td>Default value: 10. Value must be less than or equal to 20.</td> </tr> </tbody> </table>	Name	Located in	Mandatory	Schema	Description	<ID>	URL	Yes	int	Alert identifier	start	Querystring	No	int	Default value: 0.	rows	Querystring	No	int	Default value: 10. Value must be less than or equal to 20.
Name	Located in	Mandatory	Schema	Description																	
<ID>	URL	Yes	int	Alert identifier																	
start	Querystring	No	int	Default value: 0.																	
rows	Querystring	No	int	Default value: 10. Value must be less than or equal to 20.																	
<b>Supported response formats</b>	<table border="1"> <thead> <tr> <th>Format</th> <th>Mime type</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table>	Format	Mime type	JSON	application/json	XML	text/xml														
Format	Mime type																				
JSON	application/json																				
XML	text/xml																				
<b>Responses</b>	<table border="1"> <thead> <tr> <th>Code</th> <th>Description</th> <th>Schema(JSON)</th> </tr> </thead> <tbody> <tr> <td>200</td> <td>Success. Provides list of alert's viewid.</td> <td> <pre>{   "count":     int,   ,</pre> </td> </tr> </tbody> </table>	Code	Description	Schema(JSON)	200	Success. Provides list of alert's viewid.	<pre>{   "count":     int,   ,</pre>														
Code	Description	Schema(JSON)																			
200	Success. Provides list of alert's viewid.	<pre>{   "count":     int,   ,</pre>																			

```
"Views": [
  {
    id": "string",
    email_sen_ton": "string(UFC Form
```

```
at) , " Document Count" : int }  
]
```

401

Unauthorized Access.  
Client receives this  
code when  
"Authorization"  
header is passed in  
request but token  
validation fails

```
{  
  "Message": "string"  
}
```

500

Internal error

```
{
  "code" : string,
  "message" : string,
  "error" : string
}
```

**Sample Call**

```

var settings = {
  "crossDomain": true,
  "url": "https://api.
legalintelligence.com/alerts/1
/views",
  "method": "GET",
  "headers": {
    "X-SubSiteCode": "LI",
    "Authorization": "Bearer
eyJ0eXAiOiJKV1QiLCJhbGciOiJIUz
I1NiJ9.eyJsaTp..MX0.
6pNugdmqnmix38pETbyGI_zchmBCBw
FQt_tFNBTk55c",
    "Accept": "application
/json"
  }
}

$.ajax(settings).done
(function (response) {
  console.log(response);
});

```

**Response Models****Response**

Field	Type	Description
Count	int	Count of views.
Views	object[]	List of views

**View**

Field	Type	Description
Id	string	ViewId of alert.
EmailSentOn	string	Date of sent email alert in UTC date format
DocumentCount	string	Number of document sent in mail

**Notes****Summary**

Provides replay alert information

**Description**

This endpoint provides information of replay alert. This endpoint is available to authenticated users.

**URL**

/alerts/replay/&lt;viewId&gt;

**Method**

GET

**Available in version**

v2

**Headers**

Name	Mandatory	Description						
Accept	Yes	<table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table>	Output format	value	JSON	application/json	XML	text/xml
Output format	value							
JSON	application/json							
XML	text/xml							
X-SubSiteCode	No	Default value: LI						
Authorization	Yes	e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJsa..XO.6pNugdmmqmix38pETbyGI_zchmBCBwFQt_tFNB Tk55c						

**Parameters**

Name	Located in	Mandatory	Schema	Description
<viewId>	URL	Yes	string	view identifier
start	Querystring	No	int	Default value: 0. Value must be greater than or equal to 0.
rows	Querystring	No	int	Default value: 20. Value must be less than or equal to 40.
fq	Querystring	No	string[]	Navigation filters. Multiple fq querystring allowed.

**Supported response formats**

Format	Mime type
JSON	application/json
XML	text/xml

**Responses**

Code	Description	Schema (JSON)
200	Success. Provides information about replay alert.	<pre>{   "Content":   "Alert"</pre>

```
e  
r  
t  
M  
e  
t  
a  
d  
a  
t  
a  
:  
{  
  "Name":  
  string,  
  "SearchType":  
  string,  
  "E
```

```
m a i l s e n t o n " : d a t e t i m e ( U T C F o r m a t ) }  
" D o c u m e n t s " : [ {  
" I d
```

" : s t r i n g , " F i t t l e " : s t r i n g , " s u b t i t l e " : s t r i n g , " D i s p l a y

F i t t l e " : s t r i n g , " D i s p l a y S u b t i t l e " : s t r i n g , " S u m m a r y " : s t

r  
i  
n  
g  
,  
"  
U  
r  
l  
"  
:  
s  
t  
r  
i  
n  
g  
,  
"  
O  
r  
i  
g  
i  
n  
a  
l  
U  
r  
l  
"  
:  
s  
t  
r  
i  
n  
g  
,  
"  
J  
u  
r  
i  
s  
d  
i  
c  
t  
i

o n " : s t r i n g , " D o c u m e n t T y p e " : s t r i n g , " L a w A r e a " : s t r i n g [ ]

, " I S S U I N G I N S T I T U T I O N " : S T R I N G , " C A S E N U M B E R " : S T R I N G , "

P  
u  
b  
l  
i  
c  
a  
t  
i  
o  
n  
N  
u  
m  
b  
e  
r  
:  
:  
s  
t  
r  
i  
n  
g  
,  
"  
I  
s  
s  
u  
e  
N  
u  
m  
b  
e  
r  
:  
:  
s  
t  
r  
i  
n  
g  
,  
"  
P  
u  
b

l  
i  
c  
c  
a  
t  
i  
o  
n  
D  
a  
t  
e  
"  
:  
i  
n  
t  
,  
"  
E  
n  
a  
c  
t  
m  
e  
n  
t  
D  
a  
t  
e  
"  
:  
i  
n  
t  
,  
"  
D  
a  
t  
e  
A  
d  
d  
e  
d  
"  
:  
i

```
nt, "sources": string[], "urlWithAuthToken": string
```

g  
}  
],  
,"  
N  
a  
v  
i  
g  
a  
t  
i  
o  
n  
G  
r  
o  
u  
p  
s  
":  
[  
{  
,"  
T  
e  
x  
t  
":  
s  
t  
r  
i  
n  
g  
,  
,"  
N  
a  
v  
i  
g  
a

t  
i  
o  
n  
s  
:  
[  
{  
"Text":  
string,  
,  
"Filter":  
string,  
,  
"Count":  
in

		<pre>t } ] } ] }</pre>
401	Unauthorized Access. Client receives this code when "Authorization" header is passed in request but token validation fails	<pre>{   "   M   e   s   s   a   g   e   "   :   s   t   r   i   n   g }</pre>
500	Internal error	

```
{
  = CODE = : string ,
  = MESSAGE = : string ,
  = ERRORID = : string }
}
```

**Sample Call**

```
var settings = {
  "crossDomain": true,
  "url": "https://api.
legalintelligence.com/alerts
/replay/<viewId>",
  "method": "GET",
  "headers": {
    "X-SubSiteCode": "LI",
    "Authorization": "Bearer
eyJ0eXAiOiJKV1QiLCJhbGciOiJIUz
IlNiJ9.eyJsaTp..MX0.
6pNugdmqnmix38pETbyGI_zchmBCBw
FQt_tFNBTk55c",
    "Accept": "application
/json"
  }
}

$.ajax(settings).done
(function (response) {
  console.log(response);
});
```

**Response Models**

Response		
Field	Type	Description
Count	int	Count of documents.
AlertMetadata	object	Alert detail
Documents	object[]	List of documents
NavigationGroups	object	Navigation detail

AlertMetadata		
Field	Type	Description
Name	string	Name of alert.
SearchType	string	Search type of alert
EmailSentOn	string	Date of sent email alert in UTC date format

Document		
Field	Type	Description
Id	string	Document identifier
Title	string	Title of document
Subtitle	string	Subtitle of document
DisplayTitle	string	DisplayTitle of document
DisplaySubtitle	string	DisplaySubtitle of document
Summary	string	Summary of document
Url	string	Url of document
OriginalUrl	string	OriginalUrl of document
Jurisdiction	string	Jurisdiction of document
DocumentType	string	DocumentType of document
LawArea	string[]	List of lawarea
IssuingInstitution	string	IssuingInstitutionof document
CaseNumber	string	CaseNumber of document
PublicationNumber	string	PublicationNumber of document
IssueNumber	string	IssueNumber of document
PublicationDate	string	Date of publication
EnactmentDate	string	Date of enactment
DateAdded	string	Date added of document
Sources	string[]	List of source
UrlWithAutoLogOnToken	string	Auto logon document open url

NavigationGroup		
Field	Type	Description
Text	string	Name of navigation group
Navigations	object[]	List of navigations

Navigation		
Field	Type	Description
Text	string	Name of navigation
Filter	string	Filter of navigation
Count	int	count of filters

Notes