

# Library

<b>Summary</b>	LI Library (Digibieb) Sources																																						
<b>Description</b>	This endpoint returns a list of sources belonging to LI Library. The endpoint is available only to authenticated users.																																						
<b>URL</b>	/library/sources																																						
<b>Method</b>	GET																																						
<b>Available in version</b>	v2																																						
<b>Headers</b>	<table border="1"> <thead> <tr> <th>Name</th> <th>Mandatory</th> <th colspan="3">Description</th> </tr> </thead> <tbody> <tr> <td rowspan="3">Accept</td> <td rowspan="3">No</td> <td colspan="3"> <table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/JSON</td> </tr> <tr> <td>XML</td> <td>text/XML</td> </tr> </tbody> </table> </td> </tr> <tr> <td colspan="3">Default: JSON</td> </tr> <tr> <td colspan="5">Note: It is recommended that client application not rely on default output and always pass valid Accept header.</td> </tr> <tr> <td>X-SubSiteCode</td> <td>No</td> <td colspan="3">Default value: LI</td> </tr> <tr> <td>Authorization</td> <td>Yes</td> <td colspan="3">e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJsa..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c</td> </tr> </tbody> </table>					Name	Mandatory	Description			Accept	No	<table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/JSON</td> </tr> <tr> <td>XML</td> <td>text/XML</td> </tr> </tbody> </table>			Output format	value	JSON	application/JSON	XML	text/XML	Default: JSON			Note: It is recommended that client application not rely on default output and always pass valid Accept header.					X-SubSiteCode	No	Default value: LI			Authorization	Yes	e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJsa..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c		
	Name	Mandatory	Description																																				
	Accept	No	<table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/JSON</td> </tr> <tr> <td>XML</td> <td>text/XML</td> </tr> </tbody> </table>			Output format	value	JSON	application/JSON	XML			text/XML																										
			Output format	value																																			
JSON			application/JSON																																				
XML	text/XML																																						
Default: JSON																																							
Note: It is recommended that client application not rely on default output and always pass valid Accept header.																																							
X-SubSiteCode	No	Default value: LI																																					
Authorization	Yes	e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJsa..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c																																					
<b>Parameters</b>	<table border="1"> <thead> <tr> <th>Name</th> <th>Located in</th> <th>Mandatory</th> <th>Schema</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>start</td> <td>Querystring</td> <td>No</td> <td>int</td> <td>Default value: 0. The value must be greater than or equal to 0 and less than or equal to 10000.</td> </tr> <tr> <td>rows</td> <td>Querystring</td> <td>No</td> <td>int</td> <td>Default value: 20. The value must be less than or equal to 40.</td> </tr> <tr> <td>q</td> <td>Querystring</td> <td>No</td> <td>string</td> <td>Search text</td> </tr> </tbody> </table>					Name	Located in	Mandatory	Schema	Description	start	Querystring	No	int	Default value: 0. The value must be greater than or equal to 0 and less than or equal to 10000.	rows	Querystring	No	int	Default value: 20. The value must be less than or equal to 40.	q	Querystring	No	string	Search text														
	Name	Located in	Mandatory	Schema	Description																																		
	start	Querystring	No	int	Default value: 0. The value must be greater than or equal to 0 and less than or equal to 10000.																																		
	rows	Querystring	No	int	Default value: 20. The value must be less than or equal to 40.																																		
q	Querystring	No	string	Search text																																			
<b>Supported response formats</b>	<table border="1"> <thead> <tr> <th>Format</th> <th>Mime type</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table>					Format	Mime type	JSON	application/json	XML	text/xml																												
	Format	Mime type																																					
	JSON	application/json																																					
XML	text/xml																																						

Responses	Code	Description	Schema (JSON)
	200	Success. Provide total sources count, list of sources.	<pre> {   "Count": int,   "Sources": [     {       "DateAdded": string,       "Publisher": string,       "SourceID": string,       "Source": string,       "ISBNISSN": string     }   ] } </pre>
	400	Bad request. The client receives this code when data validation fails.	<pre> {   "Message": string,   "ModelState": {     "&lt;PARAMETER_NAME&gt;":     [       string     ]   } } </pre>
	401	Unauthorized. The client receives this code when "Authorization" header passed in request and token validation fail	<pre> {   "Message": string } </pre>
	500	Internal error	<pre> {   "Code": string,   "Message": string,   "ErrorId": string } </pre>
Sample Call	<pre> var settings = {   "crossDomain": true,   "url": "https://api.legalintelligence.com/library/sources",   "method": "GET",   "headers": {     "X-SubSiteCode": "LI",     "Authorization": "Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJzaTp..MX0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c",     "Accept": "application/json"   } }  \$.ajax(settings).done(function (response) {   console.log(response); }); </pre>		

**Response Models****Response**

Field	Type	Description
Count	int	Total count of sources.
Sources	object[]	List of sources

**Library**

Field	Type	Description
DateAdded	int	Date when Source added in LI. Format: yyyyMMdd
Publisher	string	Name of publisher
SourceID	int	Source Identifier
Source	string	Name of source
ISBNISSN	string	ISBNISSN number

**Notes**