

# Documents

<b>Summary</b>	Provides document content.										
<b>Description</b>	This endpoint provide document content. The endpoint is available for only authenticated users.										
<b>URL</b>	/documents/<DOCUMENT_ID>										
<b>Method</b>	GET										
<b>Available in version</b>	v1										
<b>Headers</b>	<table border="1"><thead><tr><th>Name</th><th>Mandatory</th><th>Description</th></tr></thead><tbody><tr><td>X-SubSiteCode</td><td>No</td><td>Default value: LI</td></tr><tr><td>Authorization</td><td>Yes</td><td>e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJza..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c</td></tr></tbody></table>	Name	Mandatory	Description	X-SubSiteCode	No	Default value: LI	Authorization	Yes	e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJza..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c	
Name	Mandatory	Description									
X-SubSiteCode	No	Default value: LI									
Authorization	Yes	e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJza..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c									
<b>Parameters</b>	<table border="1"><thead><tr><th>Name</th><th>Located in</th><th>Mandatory</th><th>Schema</th><th>Description</th></tr></thead><tbody><tr><td>&lt;DOCUMENT_ID&gt;</td><td>URL</td><td>Yes</td><td>string</td><td>ID of document.</td></tr></tbody></table>	Name	Located in	Mandatory	Schema	Description	<DOCUMENT_ID>	URL	Yes	string	ID of document.
Name	Located in	Mandatory	Schema	Description							
<DOCUMENT_ID>	URL	Yes	string	ID of document.							
<b>Supported response formats</b>	Document type can be PDF, Html, Word document etc. Content type header included in response so client application can identify type of document and display it accordingly.										

Responses		
Code	Description	Schema (JSON)
200	Success. Provide document content.	
404	Document not available or no access to user.	
400	Bad request. Client receives this code when data validation fails.	<pre>{   "Message": string,   "ModelState": {     "&lt;PARAMETER_NAME&gt;": [       string     ]   } }</pre>
401	Unauthorized. Client receive this code when authorization token validation fail	<pre>{   "Message": string }</pre>
500	Internal error	<pre>{   "Code": string,   "Message": string,   "ErrorId": string }</pre>
<b>Sample Call</b>	<pre>var settings = {   "crossDomain": true,   "url": "https://api.legalintelligence.com/documents/56565656",   "method": "GET",   "headers": {     "x-subsitecode": "LI",     "authorization": "Bearer eyJ0eXAiOiJKV..pETbyGI_zchmBCBwFQt_tFNBTk55c"   } }  \$.ajax(settings).done(function (response) {   console.log(response); });</pre>	
<b>Response Models</b>	NA	

