

Sources

Summary	Provides list of sources																																						
Description	This endpoint returns list of sources and navigation/filter options. The endpoint is available only to authenticated users.																																						
URL	/sources																																						
Method	GET																																						
Available in version	v1, v2																																						
Headers	<table border="1"> <thead> <tr> <th>Name</th> <th>Mandatory</th> <th colspan="3">Description</th> </tr> </thead> <tbody> <tr> <td rowspan="3">Accept</td> <td rowspan="3">No</td> <td colspan="3"> <table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table> </td> </tr> <tr> <td colspan="3">Default: JSON</td> </tr> <tr> <td colspan="5">Note: It is recommended that client application not rely on default output and always pass valid Accept header.</td> </tr> <tr> <td>X-SubSiteCode</td> <td>No</td> <td colspan="3">Default value: LI</td> </tr> <tr> <td>Authorization</td> <td>Yes</td> <td colspan="3">e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJsa..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBtk55c</td> </tr> </tbody> </table>					Name	Mandatory	Description			Accept	No	<table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table>			Output format	value	JSON	application/json	XML	text/xml	Default: JSON			Note: It is recommended that client application not rely on default output and always pass valid Accept header.					X-SubSiteCode	No	Default value: LI			Authorization	Yes	e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJsa..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBtk55c		
	Name	Mandatory	Description																																				
	Accept	No	<table border="1"> <thead> <tr> <th>Output format</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table>			Output format	value	JSON	application/json	XML			text/xml																										
			Output format	value																																			
JSON			application/json																																				
XML	text/xml																																						
Default: JSON																																							
Note: It is recommended that client application not rely on default output and always pass valid Accept header.																																							
X-SubSiteCode	No	Default value: LI																																					
Authorization	Yes	e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJsa..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBtk55c																																					
Parameters	<table border="1"> <thead> <tr> <th>Name</th> <th>Located in</th> <th>Mandatory</th> <th>Schema</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>start</td> <td>Querystring</td> <td>No</td> <td>int</td> <td>Default value: 0. Value must be greater than or equal to 0 and less than or equal to 10000.</td> </tr> <tr> <td>rows</td> <td>Querystring</td> <td>No</td> <td>int</td> <td>Default value: 20. Value must be less than or equal to 40.</td> </tr> <tr> <td>sort</td> <td>Querystring</td> <td>No</td> <td>string</td> <td>Default value: NAME Allowed sorting types are: <ul style="list-style-type: none"> NAME PUBLICATIONDATE CURRENTCONTENT </td> </tr> <tr> <td>q</td> <td>Querystring</td> <td>No</td> <td>string</td> <td>Search text</td> </tr> <tr> <td>fq</td> <td>Querystring</td> <td>No</td> <td>string[]</td> <td>Navigation filters. Multiple fq querystring allowed. e.g. fq=Source_HF%3a0%7c200_Tijdschriften&fq=LawArea%3aAlgemeen</td> </tr> </tbody> </table>					Name	Located in	Mandatory	Schema	Description	start	Querystring	No	int	Default value: 0. Value must be greater than or equal to 0 and less than or equal to 10000.	rows	Querystring	No	int	Default value: 20. Value must be less than or equal to 40.	sort	Querystring	No	string	Default value: NAME Allowed sorting types are: <ul style="list-style-type: none"> NAME PUBLICATIONDATE CURRENTCONTENT 	q	Querystring	No	string	Search text	fq	Querystring	No	string[]	Navigation filters. Multiple fq querystring allowed. e.g. fq=Source_HF%3a0%7c200_Tijdschriften&fq=LawArea%3aAlgemeen				
	Name	Located in	Mandatory	Schema	Description																																		
	start	Querystring	No	int	Default value: 0. Value must be greater than or equal to 0 and less than or equal to 10000.																																		
	rows	Querystring	No	int	Default value: 20. Value must be less than or equal to 40.																																		
	sort	Querystring	No	string	Default value: NAME Allowed sorting types are: <ul style="list-style-type: none"> NAME PUBLICATIONDATE CURRENTCONTENT 																																		
	q	Querystring	No	string	Search text																																		
	fq	Querystring	No	string[]	Navigation filters. Multiple fq querystring allowed. e.g. fq=Source_HF%3a0%7c200_Tijdschriften&fq=LawArea%3aAlgemeen																																		
Supported response formats	<table border="1"> <thead> <tr> <th>Format</th> <th>Mime type</th> </tr> </thead> <tbody> <tr> <td>JSON</td> <td>application/json</td> </tr> <tr> <td>XML</td> <td>text/xml</td> </tr> </tbody> </table>		Format	Mime type	JSON	application/json	XML	text/xml																															
	Format	Mime type																																					
	JSON	application/json																																					
XML	text/xml																																						

Responses	Code	Description	Schema (JSON)
	200	Success. Provide total source count, list of source and navigation.	<pre> { "Count": int, "Sources": [{ "DisplayCode": string, "Title": string, "Publisher": string, "SourceTypes": [string], "IssueNumber": string, "PublicationDate": string }], "NavigationGroups": [{ "Text": string, "Navigations": [{ "Text": string, "Filter": string, "Count": int }], "Field": string }] } </pre>
	400	Bad request. Client receives this code when data validation fails.	<pre> { "Message": string, "ModelState": { "<PARAMETER_NAME>": [string] } } </pre>
	401	Unauthorized. Client receive this code when "Authorization" header passed in request and token validation fail	<pre> { "Message": string } </pre>
	500	Internal error	<pre> { "Code": string, "Message": string, "ErrorId": string } </pre>

Sample Call

```

var settings = {
  "crossDomain": true,
  "url": "https://api.legalintelligence.com/sources",
  "method": "GET",
  "headers": {
    "X-SubSiteCode": "LI",
    "Authorization": "Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJsaXNpdjIzLnMxOj06pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c",
    "Accept": "application/json"
  }
}

$.ajax(settings).done(function (response) {
  console.log(response);
});

```

Response Models

Response		
Field	Type	Description
Count	int	Total count of source.
Sources	object[]	List of Source
NavigationGroups	object[]	List of NavigationGroup

Source		
Field	Type	Description
DisplayCode	string	Display code of source.
Title	string	Name of source
Publisher	string	Name of publisher
SourceTypes	string[]	List of source type
IssueNumber	string	Latest issue number of source
PublicationDate	string	Latest publication date of source

NavigationGroup		
Field	Type	Description
Text	string	Display text of group
Navigations	object[]	List of Navigation
Field	string	Field name

Navigation		
Field	Type	Description
Text	string	Display text of navigation
Filter	string	Filter of navigation. Used in fq request parameter.
Count	int	Total source in this category.

Notes

Summary	Provides detail of a source
Description	This endpoint provides information about a source. The endpoint is available only to authenticated users.
URL	/sources/detail?code=<DISPLAY_CODE>
Comment	It is advised to URL encode the <DISPLAY_CODE> part, so that AV&S becomes AV%26S
Method	GET
Available in version	v2

Headers	Name	Mandatory	Description		
	Accept	Yes	Output format		value
			JSON	application/json	
			XML	text/xml	
X-SubSiteCode	No	Default value: LI			
Authorization	Yes	e.g. Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUz11NiJ9.eyJsa..X0.6pNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c			
Parameters	Name	Located in	Mandatory	Schema	Description
	code	Querystring	Yes	string	Display code of source.
Supported response formats	Format	Mime type			
	JSON	application/json			
	XML	text/xml			
Responses	Code	Description			Schema(JSON)
	200	Success. Provides detail of a source.			<pre>{ "DisplayCode": string, "Title": string, "Publisher": string, "LawAreas": [string], "Summary": string, "IssueNumber": string, "PublicationDate": string, "SpecialFeatures": string, "HierarchyBreadcrumb": [string], "PublicationStart": string, "PublicationEnd": string }</pre>
	401	Unauthorized. Client receive this code when "Authorization" header passed in request and token validation fail			<pre>{ "Message": string }</pre>
	500	Internal error			<pre>{ "Code": string, "Message": string, "ErrorId": string }</pre>

Sample Call

```

var settings = {
  "crossDomain": true,
  "url": "https://api.legalintelligence.com/sources/detail?code=NJ",
  "method": "GET",
  "headers": {
    "X-SubSiteCode": "LI",
    "Authorization": "Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJsaXNpdCI6ImNugdmqnmix38pETbyGI_zchmBCBwFQt_tFNBTk55c",
    "Accept": "application/json"
  }
}

$.ajax(settings).done(function (response) {
  console.log(response);
});

```

Response Models

Source		
Field	Type	Description
DisplayCode	string	Display code of source.
Title	string	Name of source
Publisher	string	Name of publisher
LawAreas	string[]	List of LawArea
Summary	string	Summary of source
IssueNumber	string	Latest issue number of source
PublicationDate	string	Latest publication date of source
SpecialFeatures	string	Special features of source
HierarchyBreadcrumb	string[]	Logical breadcrumb of source
PublicationStart	string	Publication start information
PublicationEnd	string	Publication end information

Notes