

Token

Summary	Token endpoint																							
Description	This endpoint authenticates user, and provides token to access protected endpoints. API uses OAuth2 authentication mechanism.																							
URL	/token																							
Method	POST																							
Available in version	v1,v2																							
Headers	<table border="1"><thead><tr><th>Name</th><th>Mandatory</th><th>Description</th></tr></thead><tbody><tr><td>Content-Type</td><td>Yes</td><td>Use "application/x-www-form-urlencoded"</td></tr><tr><td>X-SubSiteCode</td><td>No</td><td>Default value: LI</td></tr></tbody></table>				Name	Mandatory	Description	Content-Type	Yes	Use "application/x-www-form-urlencoded"	X-SubSiteCode	No	Default value: LI											
Name	Mandatory	Description																						
Content-Type	Yes	Use "application/x-www-form-urlencoded"																						
X-SubSiteCode	No	Default value: LI																						
Parameters	<table border="1"><thead><tr><th>Name</th><th>Located in</th><th>Mandatory</th><th>Schema</th><th>Description</th></tr></thead><tbody><tr><td>grant_type</td><td>Body</td><td>Yes</td><td>string</td><td>Use "client_credentials" as value</td></tr><tr><td>client_id</td><td>Body</td><td>Yes</td><td>string</td><td>Use your registered email address with Legal Intelligence website, as value.</td></tr><tr><td>client_secret</td><td>Body</td><td>Yes</td><td>string</td><td>Use secret key provided by Legal Intelligence, as value.</td></tr></tbody></table>				Name	Located in	Mandatory	Schema	Description	grant_type	Body	Yes	string	Use "client_credentials" as value	client_id	Body	Yes	string	Use your registered email address with Legal Intelligence website, as value.	client_secret	Body	Yes	string	Use secret key provided by Legal Intelligence, as value.
Name	Located in	Mandatory	Schema	Description																				
grant_type	Body	Yes	string	Use "client_credentials" as value																				
client_id	Body	Yes	string	Use your registered email address with Legal Intelligence website, as value.																				
client_secret	Body	Yes	string	Use secret key provided by Legal Intelligence, as value.																				
Supported response formats	<table border="1"><thead><tr><th>Format</th><th>Mime type</th></tr></thead><tbody><tr><td>JSON</td><td>application/json</td></tr></tbody></table> <p>Note: Endpoint always return JSON response as defined in RFC6749</p>				Format	Mime type	JSON	application/json																
Format	Mime type																							
JSON	application/json																							
Response	<table border="1"><thead><tr><th>Status Code</th><th>Description</th><th>Schema (JSON)</th></tr></thead><tbody><tr><td>200</td><td>Success. Provides token with expiry information.</td><td><pre>{ "access_token": string, "token_type": string, "expires_in": int }</pre></td></tr><tr><td>400</td><td>Bad request. Client may receive this code due to following reason:<ul style="list-style-type: none">Invalid client (Authentication fail)</td><td><pre>{ "error": string, "error_description": string }</pre></td></tr><tr><td>500</td><td>Internal error. In case something went wrong in processing the request by the server.</td><td><pre>{ "Code": string, "Message": string, "ErrorId": string }</pre></td></tr></tbody></table>				Status Code	Description	Schema (JSON)	200	Success. Provides token with expiry information.	<pre>{ "access_token": string, "token_type": string, "expires_in": int }</pre>	400	Bad request. Client may receive this code due to following reason: <ul style="list-style-type: none">Invalid client (Authentication fail)	<pre>{ "error": string, "error_description": string }</pre>	500	Internal error. In case something went wrong in processing the request by the server.	<pre>{ "Code": string, "Message": string, "ErrorId": string }</pre>								
Status Code	Description	Schema (JSON)																						
200	Success. Provides token with expiry information.	<pre>{ "access_token": string, "token_type": string, "expires_in": int }</pre>																						
400	Bad request. Client may receive this code due to following reason: <ul style="list-style-type: none">Invalid client (Authentication fail)	<pre>{ "error": string, "error_description": string }</pre>																						
500	Internal error. In case something went wrong in processing the request by the server.	<pre>{ "Code": string, "Message": string, "ErrorId": string }</pre>																						

Sample Call	<pre>var settings = { "crossDomain": true, "url": "https://api.legalintelligence.com/token", "method": "POST", "headers": { "Content-Type": "application/x-www-form-urlencoded", "X-SubSiteCode": "LI", "cache-control": "no-cache" }, "data": { "grant_type": "client_credentials", "client_id": "apiuser1@legalintelligence.com", "client_secret": "C6402106-F190-42E4-B276-6F646C51E79B" } } \$.ajax(settings).done(function (response) { console.log(response); });</pre>
Response Models	NA
Notes	